



ODVIE

1U IP Video Server






- Fully integrated with CathexisVision VMS
 Designed as the perfect compliment to the software suite extensive capabilities of the CathexisVision
- High Performance Database
 The disk spanning capabilities of our Advanced Database supports up to 250Mb/s recording throughput
- Engineered for stability & reliability
 Quality materials, excellent design and
 construction anticipates challenging
 environments.
- Enterprise Class Storage up to 40TB
 Enterprise-grade Hard Drives
- High End Desktop Motherboards
 High ESD and High Temperature protection provided by long life components
- Compact Rack Mount Chassis
 Rack rails are an available optional extra.
- Server-grade PSUs
 Energy Efficient (80 Plus) Power Supplies

- Solid State Operating System drive
 Ensures a stable and reliable operating environment with no moving parts
- Linux or Windows OS
 Choose between Linux and Windows OS to suit your preferred IT infrastructure.
- Health Monitoring Watchdog
 A comprehensive suite of self-diagnostic functions detect and report hardware and software issues
- Flexible User Interfaces
 Local, Client, and Mobile applications for Live and Review
- Enterprise or Multi-site compatible
 Can be connected to a CathexisVision
 Enterprise or Multi-site estates
- 2 Year Hardware Warranty
 A comprehensive hardware replacement warranty for total peace of mind

Server Specifications



Chassis	Туре	1U Rack Mount
	Rail Kit	On Request
	Dimensions	250 x 430 x 43.5mm (D x W x H)
	3.5" Internal Bays	2
	Front Panel USB 3.0	2
Processor	Model	i3-12100
	Core Count	4 Cores, 8 Threads
	Clock Speed	Up to 4.3GHz
Memory	Capacity	8GB DDR4
Graphics	Туре	Intel UHD Graphics 730
	Max Monitors	3 incl: 1x HDMl2.1b, 1x DisplayPort 1.4a, 1x VGA 1 2
	Discrete Graphics	Not Supported
PSU	Туре	FlexATX 80+ Bronze PSU
OS	Туре	Windows 11 Pro or Ubuntu
Network	1Gb	1x 1Gb LAN
Motherboard	Туре	Mini ITX Motherboard
	Chipset	Intel H610
Rear Panel I/O	Display Outputs	As above
	Network	As above
	USB 3.2 Gen1 (Type A)	2
	USB 2.0 (Type A)	2
	Line Out	1x 2.1 Channel 3.5mm
	Line In	1x Mic In 3.5mm
Storage	Max Standard Storage	40TB
	RAID	Not Supported
Throughput	1Gb NIC	250Mb/s



While Cathexis has made every effort to ensure the accuracy of this document, there is no guarantee of accuracy, neither explicit, nor implied Specifications subject to change without notice.

