

CobiCabling CAT 6A U/FTP Cable LSOH 700MHz, 4x2xAWG23



PRODUCT DESCRIPTION

CobiCabling Category 6A cable shielded LSOH is manufactured and tested to exceed EN 50173-1:2018-07, EN 50173-1:2011, ISO/IEC 11801 Edition 2.2 with exceptional margin on all parameters. Our CAT6A cable is designed for high speed LAN applications including 10 Gigabit Ethernet, combined with our patch panels and connectivity product it forms a truly reliable foundation for any network.

The individually wrapped pairs ensure best transmission and eliminate alien crosstalk as well as NEXT problems.







700MHz working frequency (CAT6A, Class EA)

25-years manufacturers warranty

Sequential metre markings

LS0H outer sheath

Features:

Individually shielded pairs

Euroclass Dca s2, d2, a1

CONFORMS TO:

- EN 50173-1:2018-07
- ISO/IEC 11801 Edition 2.2
- ANSI/TIA-568-C.0/C.1/C.2
- IEC 60754-2
- IEC 60332-1

TYPICAL APPLICATIONS:

- 10GBase-T 10 Gigabit Ethernet
- Composite Video;
- PoE, PoE+, 4PPoE

Technical spec	Details
Frequency	Tested up to 700MHz
Outer sheath	LS0H green colour
Category compliance	6A
Shield	U/FTP
Metre mark	From 500 to 0 (every 1m)
NVP	77% (0,77)
Overall diameter	6,7mm
Conductor diameter	23AWG
Euroclass	Dca- s2, d2, a1
Temperature range	During installation –10°C to +50°C, After installation –30°C to +70°C

Part numbers	Name
C23-1330	CobiCabling CAT 6A U/FTP Cable LSOH 700MHz, 4x2xAWG23